

M A T E R I A L S A F E T Y D A T A S H E E T
CLEAR HEAVY DUTY WALLPAPER

Page: 1

PRODUCT NAME: CLEAR HEAVY DUTY WALLPAPER
PRODUCT CODE: LA-644HMIS CODES: H F R P
0 0 0 A

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: LANCO MFG. CORP.
ADDRESS : URB. APONTE #5
SAN LORENZO, PUERTO RICO
00754
EMERGENCY PHONE : (787) 736-4200 DATE PRINTED : 12/05/02
INFORMATION PHONE : (787) 736-4200 NAME OF PREPARER : LANCO MFG.CORP.

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT

WATER	7732-18-5		

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: n/a SPECIFIC GRAVITY (H2O=1): 1.01
VAPOR DENSITY: LIGHTER THAN AIR EVAPORATION RATE: UNKNOWN
COATING V.O.C.: 0.17 lb/gal MATERIAL V.O.C.: 0.05 lb/gal
SOLUBILITY IN WATER: AQUEOUS SYSTEM
APPEARANCE AND ODOR: SLOW ODOR

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: n/a METHOD USED: n/a
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: n/a UPPER: n/a

EXTINGUISHING MEDIA: CO2, WATER FOG, OTHER

SPECIAL FIREFIGHTING PROCEDURES
SUMMON PROFESSIONAL FIREFIGHTERS. USE FULL PROTECTIVE EQUIPMENT INCLUDING SELF
CONTAINED BREATHING APPARATUS. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS
USED, FOG NOZZLES ARE PREFERABLE.

UNUSUAL FIRE AND EXPLOSION HAZARDS
DUE TO PRESSURE BUILD-UP, CLOSED CONTAINERS EXPOSED TO EXTREME HEAT MAY EXPLODE
DURING EMERGENCY CONDITIONS, OVEREXPOSURE TO DECOMPOSITION PRODUCT MAY CAUSE A
HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. OBTAIN MEDICAL
ATTENTION.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE
CONDITIONS TO AVOID

INCOMPATIBILITY (MATERIALS TO AVOID)
NONE

HAZARDOUS DECOMPOSITION OR BYPRODUCTS
MAY CAUSE HAZARDOUS FUMES WHEN HEATED TO DECOMPOSITION. FUMES MAY CONTAIN
CARBON MONOXIDE, CARBON DIOXIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====
 M A T E R I A L S A F E T Y D A T A S H E E T
 CLEAR HEAVY DUTY WALLPAPER Page: 2

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
 IRRITATION OF THE RESPIRATORY TRACT; HEADACHE, NAUSEA, DIZZINESS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE
 IN CASE OF EYE CONTACT, FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15
 MINUTES. GET MEDICAL ASSISTANT.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
 WASH AFFECTED SKIN AREAS THOROUGHLY WITH SOAP AND WATER. CONSULT A PHYSICIAN IF
 IRRITATION PERSISTS.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
 DRINK 1 OR 2 GLASSES OF WATER DILUTE. DO NOT INDUCE VOMITING. CONSULT PHYSICIAN
 OR POISON CONTROL CENTER IMMEDIATELY. TREAT SYMPTOMATICALLY.

HEALTH HAZARDS (ACUTE AND CHRONIC)
 PROLONGED AND REPEATED BREATHING OF SPRAY MIST AND/OR SANDING DUST OVER A PERIOD
 OF YEARS MAY CAUSE DUST DISEASE OF THE LUNGS.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No
 NONE

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE
 NONE WHEN USED IN ACORDANCE WITH SAFE HANDLING AND USE INFORMATION.

EMERGENCY AND FIRST AID PROCEDURES
 IF BREATHED: REMOVED TO FRESH AIR. IF IN EYES: IN CASE OF EYE CONTACT, FLUSH WITH
 LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. IF OF SKIN: REMOVE WITH SOAP AND
 WATER. REMOVE SOILED CLOTHING. INGESTION: INDUCE VOMITING PROMPTLY ACCORDING TO
 PHYSICIANS INSTRUCTIONS OR BY HAVING PATIENT STICK FINGER DOWN THROAT. AFTER
 VOMITING HAS BEEN INDUCED, GIVE TWO TEASPOONS OF BAKING SODA IN WATER.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
 WASH WITH WATER, BEFORE ATTEMPTING CLEAN UP, REFER TO HAZARD CAUTION INFORMATION
 IN OTHER SECTION OF THIS MATERIAL SAFETY DATA FORM. CONTAIN SPILLED MATERIAL AND
 REMOVED WITH INERT ABSORBENT. STORE IN CLOSED CONTAINER.

WASTE DISPOSAL METHOD
 DISPOSE OF IN ACORDANCE WITH LOCAL, STATE AND FEDERAL REGULATION.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
 STORE BELOW 100 F AND KEEP FROM FREEZING. KEEP CONTAINER CLOSED WHEN NOT IN USE.
 DO NOT REUSE EMPTY CONTAINER. KEEP OUT OF REACH OF CHILDREN.

OTHER PRECAUTIONS
 NONE

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION
 DO NOT BREATHE VAPORS, SPRAY MIST OR SANDING DUST. WHEN SPRAY APPLIED IN OUTDOOR
 OR OPEN AREAS WITH UNRESTRICTED VENTILATION, AND DURING SANDING OR GRINDING
 OPERATION, USE NIOSH/NSHA APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE SOLID
 AIRBORNE PARTICLES OF OVERSPRAY AND SANDING DUST.

VENTILATION

USE ONLY WITH ADEQUATE VENTILATION. PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP AIR CONTAMINATE CONCENTRATION BELOW CURRENT APPLICABLE SAFETY AND HEALTH STANDARDS IN THE MIXING.

M A T E R I A L S A F E T Y D A T A S H E E T
CLEAR HEAVY DUTY WALLPAPER

Page: 3

PROTECTIVE GLOVES
NOT REQUIRED.

EYE PROTECTION
DO NOT GET IN EYES. SAFETY EYEWEAR WITH SPLASH GUARDS ARE RECOMMENDED TO PREVENT CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT
NOT REQUIRED.

WORK/HYGIENIC PRACTICES

REMOVE AND WASH SOILED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING OR USING THE BATHROOM.

===== SECTION IX - DISCLAIMER =====

The information contained herein is based on data believed by this company to be accurate, but we do not assume any liability for its accuracy. We neither suggest nor guarantee that any hazards mentioned are the only ones which exist. The manner of that use and whether there is any infringement of patents is the sole responsibility of the user.

LA644.TXT